


## Backwater valve Staufix DN 125, Floor slab, black, Type 1



### Article information

Item no.: 720125.10S  
GTIN: 4026092076064  
Price group: 10

### Advantages

- Simple conversion to Staufix Type 2 or StaufixControl
- Flexible installation, various covers available for floor slab installation
- Simple, toolless maintenance and cleaning

### Description

The backwater valve for wastewater without sewage is equipped with one mechanical flap which closes automatically in the event of backwater and also serves as an emergency closure to be closed by hand. Thanks to the modular KESSEL system, existing systems can easily be supplemented by a second flap or be converted to the StaufixControl backwater valve.

#### Variant

Emergency closure: yes  
Mechanical backwater flaps: 1

#### General characteristics

Colour: black  
Standard: EN 13564  
Nominal size (DN): 125  
Outer diameter (OD): 125 mm  
Type of wastewater: without sewage  
Installation situation: floor slab installation  
Delivery state: Installation-ready (connection parts must be connected on site)  
Backwater protection: Type 1

#### Dimensions

Net weight: 8,2 kg

Gross weight:	10,8 kg
Groundwater resistant from lower edge of base section:	3 mm
Cutout dimension, width:	750 mm
Cutout dimension, length:	750 mm
Vertical drop between inlet and outlet:	8 mm
Installation depth:	341 - 464 mm
Vertical adjustment:	vertically adjustable upper section
Length:	511 mm
Width:	444 mm
Packaging dimension:	length
Packaging dimension:	width
Packaging dimension:	height

#### Coverage features

Type of cover:	Cover plate
Cover material:	Polymer
Colour of cover:	black
Width of cover:	366 mm
Length of cover:	366 mm
Cover locking:	Lock & Lift
Load class:	L 15 (EN 1253-1)
Tightness:	surface water resistant